CH18-44
10.3 g/t Au / 1.0 m
incl. in 2.8 g/t Au / 4.0 m

CH18-43
7.6 g/t Au / 1.0 m
incl. in 4.3 g/t Au / 2.0 m

CH18-41
5.4 g/t Au / 1.0 m
incl. in 1.1 g/t Au / 8.5 m

CH18-30
12.2 g/t Au / 0.5 m
incl. in 1.3 g/t Au / 7.3 m

CH18-35
86.1 g/t Au / 1.5 m

2W ZONE
2 ZONE
2B ZONE
SHAFT
4B ZONE
4B2 ZONE
6B ZONE
6C ZONE
6B
6C
2
4B

Legend
Current Results
Mined Stope
Gold Zone
Gold Structure
Structure

200 m

PLAN VIEW
OF LEVEL 3 (175 M)

200S
400S
600S
800S
600W
400W
200W
0E
200E
400E
600E
800E
1000E
1200E
1400E
1600E
1800E

W
E
Surface
SHAFT
6C ZONE

8.5 g/t Au / 4.2 m
13.5 g/t Au / 1.7 m
7.4 g/t Au / 2.3 m

CH18-35
86.1 g/t Au / 1.5 m

TARGET

Legend
Current Results
Mined Stope
Gold Shoot
Gold Potential Dimension
Metal Factor (MF) = Au (g/t) x True Thickness (m)
< 5
> 5
Historical Results

Quality Assurance / Quality Control

The scientifical and/or technical information has been reviewed and approved by Mr. Gaétan Lavallière, P. Geo, Ph. D. and Vice-President for Cartier Resources. Mr. Lavallière is a qualified person as defined by National Instrument 43-101.

All the current and previous drill holes results for 6C Zone are measured along the core axis.

Project Manager & Geomatician : Ronan Déroff, P. Geo., M. Sc.

200 m

LONGITUDINAL SECTION
OF 6C STRUCTURE

200m
400m
600m
800m
600W
400W
200W
0E
200E
400E
600E
800E
1000E
1200E
1400E
1600E
1800E