

BEST RESULTS

Drill hole	From m	To m	Length m	Au g/t	Ag g/t	Cu %
91-24	113.4	167.6	54.3	3.6	14.8	0.24
including	114.7	120.4	5.7	10.8	57.1	0.47
including	148.0	154.0	6.0	7.9	26.0	0.36
91-26A	74.1	130.2	56.1	5.3	11.2	0.26
including	81.3	90.4	9.1	9.9	19.4	0.28
including	121.8	129.6	7.8	10.5	21.6	0.65
91-30A	142.9	196.5	53.6	5.6	14.4	0.28
including	160.6	162.0	1.4	44.3	88.0	0.47
including	178.8	188.1	9.3	11.6	25.1	0.57
92-44	41.0	78.0	37.0	6.5	8.1	0.22
including	61.0	76.5	15.5	12.9	13.6	0.35
92-46	102.0	154.5	52.5	4.1	9.5	0.17
including	116.0	126.0	10.0	7.6	12.9	0.21
including	132.0	137.0	5.0	8.4	9.6	0.17
92-58	192.0	255.0	63.0	3.8	12.5	0.22
including	198.5	201.0	2.5	8.7	26.4	0.58
including	205.0	206.0	1.0	67.8	170.0	0.25
PU-14-09	334.0	387.0	53.0	2.4	6.7	0.21
including	345.0	350.0	5.0	10.3	13.3	0.32
PU-12-01	660.0	663.0	3.0	22.8	1.2	0.01
including	662.0	663.0	1.0	65.6	2.9	0.01

Quality Assurance / Quality Control

The scientific and/or technical information presented in this document has been reviewed and approved by Mr. Gaétan Lavallière, P. Geo., Ph. D., and Vice President for Cartier Resources. Mr. Lavallière is a qualified person as defined by National Instrument 43-101.

All drill hole intersection lengths referred in this document are measured along the core axis.