CH17-15
17.1 g/t Au / 0.5 m
incl. in 7.5 g/t Au / 2.0 m
incl. in 2.1 g/t Au / 9.8 m

CH17-15
9.4 g/t Au / 0.5 m
incl. in 3.6 g/t Au / 2.0 m

CH17-19
3.8 g/t Au / 1.1 m
incl. in 0.9 g/t Au / 7.6 m

CH17-16
10.7 g/t Au / 1.0 m

CH17-19
3.2 g/t Au / 1.0 m
incl. 0.8 g/t Au / 12.1 m

CH17-19
4.4 g/t Au / 2.1 m
incl. in 1.4 g/t Au / 12.7 m

2 ZONE
2B ZONE
3W ZONE
3 ZONE
3E ZONE
3B ZONE
4 ZONE
4E ZONE
SHAFT

Legend
Current Results
Mined Stope
Gold Zone
Gold Structure
Structure

200 m

PLAN VIEW OF LEVEL 3 (175 M)

200S
400S
600S
800S
600W 400W 200W 0E 200E 400E 600E 800E 1000E 1200E 1400E 1600E 1800E

W
E
Surface
SHAFT
2 ZONE
2B ZONE

58.5 g/t Au / 2.0 m
29.4 g/t Au / 6.8 m
6.2 g/t Au / 5.9 m
4.7 g/t Au / 7.6 m
9.6 g/t Au / 2.6 m
7.0 g/t Au / 5.8 m
4.1 g/t Au / 4.7 m
6.6 g/t Au / 4.1 m
8.2 g/t Au / 7.0 m
9.4 g/t Au / 6.5 m
incl. 25.2 g/t Au / 2.0 m
incl. 56.0 g/t Au / 0.5 m

TARGET
TARGET

CH17-19
3.2 g/t Au / 1.0 m
incl. 0.8 g/t Au / 12.1 m

CH17-15
17.1 g/t Au / 0.5 m
incl. in 7.5 g/t Au / 2.0 m
incl. in 2.1 g/t Au / 9.8 m

Legend
Current Results
Previously Announced Results
Mined Stope
Gold Shoot
Gold Potential Dimension
Metal Factor (MF) = Au (g/t) x True Thickness (m)
< 5
> 5
Historical Results

Quality Assurance / Quality Control

The technical information has been reviewed and approved by Mr. Gaétan Lavallière, P. Geo, Ph. D. and Vice-President for Cartier Resources. Mr. Lavallière is a qualified person as defined by National Instrument 43-101.

All the drill holes results for 2 & 2B Zones are estimated at true thickness. All the current and previously announced results are measured along the core axis.

Project Manager & Geomatician : Ronan Déroff, P. Geo., M. Sc.

200 m

LONGITUDINAL SECTION OF 2 STRUCTURE

200m
400m
600m
800m
600W 400W 200W 0E 200E 400E 600E 800E 1000E 1200E 1400E 1600E 1800E