

**BEST DRILLING RESULTS**

<b>Drill Hole</b>	<b>From m</b>	<b>To m</b>	<b>Length m</b>	<b>Au g/t</b>
<b>VP-11-18</b>	<b>76.0</b>	<b>143.0</b>	<b>67.0</b>	<b>1.5</b>
including	76.0	77.0	1.0	30.1
including	106.0	107.0	1.0	12.5
including	125.0	126.0	1.0	24.5
<b>VP-11-11</b>	<b>174.0</b>	<b>177.0</b>	<b>3.0</b>	<b>33.2</b>
including	175.7	176.3	0.6	164.5
<b>VP-93-22</b>	<b>101.8</b>	<b>143.2</b>	<b>41.4</b>	<b>2.0</b>
including	101.8	102.8	1.0	12.6
including	138.0	143.2	5.2	11.7
<b>VP-94-45</b>	<b>228.4</b>	<b>231.0</b>	<b>2.6</b>	<b>20.2</b>
including	228.4	229.5	1.1	32.2
<b>VP-92-10</b>	<b>36.2</b>	<b>41.0</b>	<b>4.8</b>	<b>10.5</b>
including	36.2	37.0	0.8	34.3
including	39.0	39.7	0.7	20.4
<b>VP-11-05</b>	<b>28.0</b>	<b>35.0</b>	<b>7.0</b>	<b>6.3</b>
including	34.0	35.0	1.0	32.3

**BEST STRIPPING RESULTS**

<b>Channel</b>	<b>From m</b>	<b>To m</b>	<b>Length m</b>	<b>Au g/t</b>
<b>C1</b>	<b>0.0</b>	<b>5.0</b>	<b>5.0</b>	<b>21.3</b>
including	3.0	4.0	1.0	90.6
<b>R8</b>	<b>0.0</b>	<b>4.0</b>	<b>4.0</b>	<b>15.3</b>
including	2.0	3.0	1.0	47.3
<b>R6</b>	<b>0.0</b>	<b>8.0</b>	<b>8.0</b>	<b>5.9</b>
including	7.0	8.0	1.0	17.7
<b>R14</b>	<b>0.0</b>	<b>4.0</b>	<b>4.0</b>	<b>10.7</b>
including	2.0	3.0	1.0	24.5
<b>R15</b>	<b>0.0</b>	<b>3.0</b>	<b>3.0</b>	<b>13.4</b>
including	1.0	2.0	1.0	24.2

**Quality Assurance / Quality Control**

The scientific and/or technical information presented in this document has been reviewed and approved by Mr. Gaétan Lavallière, P. Geo., Ph. D. and Vice President for Cartier Resources Inc. Mr. Lavallière is a qualified person as defined by National Instrument 43-101. All drill hole and channel intersection lengths referred in this document are measured along the core and channel axis.