

**UPDATE: February 2015** 

## BEST DRILL RESULTS OF DELINEL GOLD ZONE

Drill Hole	From m	<b>To</b> m	<b>Length</b> m	<b>Au</b> g/t	Metal Factor*
DO-11-26	85.2	133.0	47.8	0.5	23.9
including	108.6	111.8	3.2	5.4	17.3
including	110.6	111.8	1.2	13.3	16.0
DO-11-25	108.1	145.3	37.2	0.3	11.1
including	123.0	124.5	1.5	4.0	6.0
DO-11-03	15.0	45.0	30.0	0.5	15.0
including	44.0	45.0	1.0	11.9	11.9
DO-11-08	59.5	89.8	30.3	0.3	9.1
including	81.8	84.3	2.5	3.0	7.5
including	82.8	83.2	0.4	11.2	4.5
DO-11-28	149.0	204.0	55.0	0.2	11
including	176.3	179.1	2.8	2.2	6.2
including	177.1	178.0	0.9	5.1	4.6
DO-11-07B	5.2	48.0	42.8	0.3	12.8
including	31.6	37.3	5.7	1.1	6.3
including	31.6	31.8	0.2	4.5	2.3
DO-11-11	8.0	42.5	34.5	0.3	10.4
including	22.4	30.5	8.1	0.9	7.3
including	22.4	22.7	0.3	6.7	2.0
DO-11-06	15.2	44.9	29.7	0.2	5.9
including	25.6	31.0	5.4	1.0	5.4
DO-14-30	175.0	176.0	1.0	25.1	25.1

## BEST DRILL RESULTS OF NORTH DELINEL GOLD ZONE

Drill Hole	From m	<b>To</b> m	<b>Length</b> m	<b>Au</b> g/t	Metal Factor*
DO-11-06	15.2	44.9	29.7	0.2	5.9
including	25.6	31.0	5.4	1.0	5.4
including	133.3	133.6	0.3	11.2	3.4
DO-11-27	85.7	150.5	64.8	0.1	6.5
including	229.0	230.4	1.4	1.2	1.7
DO-14-34	373.0	374.0	1.0	5.0	5.0

\* The Metal Factor is the grade of gold (g/t) multiplied by the length (m); it represents the amount of metal contained in the rock.

## **Quality Assurance / Quality Control**

The scientific and/or technical information presented in this document has been reviewed and approved by Mr. Gaétan Lavallière, P. Geo, Ph. D., and Vice President for Cartier Resources. Mr. Lavallière is a qualified person as defined by National Instrument 43-101

All drill hole intersection lengths referred in this document are measured along the core axis.